

Date Revised: 07/13/17

1. Product and Company Identification

Product Name : 2052 FLAT HS CLEAR URETHANE
Recommended Use: See Technical Data Sheet.

Company Identification:
Valley Paint Manufacturing
727 S. 950 West
Woods Cross, UT 84087

Information Phone: (801) 298-4581
Emergency Phone...: (801) 424-9300

2. Hazards Identification

GHS Classification
CATEGORY 2 FLAMMABLE LIQUID
CATEGORY 2A EYE IRRITATION

GHS Label Elements

Hazard Pictograms:



FLAMMABLE LIQUID AND VAPOUR. CAN CAUSE SERIOUS EYE IRRITATION. KEEP AWAY FROM HEAT, HOT SURFACES, SPARKS, OPEN FLAMES AND OTHER IGNITION SOURCES. KEEP CONTAINER TIGHTLY CLOSED. AVOID BREATHING DUST, FUME, GAS, MIST, VAPOURS AND

SPRAY. USE ONLY OUTDOORS OR IN WELL VENTILATED AREA. WEAR PROTECTIVE GLOVES, EYE PROTECTION, AND FACE PROTECTION.

3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
* XYLENE	1330-20-7	12.65
OSHA VPEL 100 PPM TWA		
OSHA VPEL 150 PPM STEL		
ACGIH TLV 100 PPM TWA		
ACGIH TLV 150 PPM STEL		
SYNTHETIC AMORPHOUS SILICA	112926-00-8	12.35
DIMETHYL CARBONATE	NA	5
* N-BUTYL ACETATE	123-86-4	6
OSHA VPEL 150 PPM TWA		
OSHA VPEL 200 PPM STEL		
ACGIH TLV 150 PPM TWA		
ACGIH TLV 200 PPM STEL		
* AROMATIC HYDROCARBON	64742-95-6	4

4. First Aid Measures

Eyes:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER. KEEP EYES WIDE OPEN WHILE RINISING. IF EYE IRRITATION PERSISTS, CONSULT SPECIALIST.

Skin:

WASH SKIN IMMEDIATELY IF ON SKIN

Ingestion:

KEEP RESPIRATORY TRACT CLEAR. IF SYMTOMS PERSIST, CALL A PHYSICIAN.

Inhalation:

CONSULT PHYSICIAN AFTER SIGNIFICANT EXPOSURE.

Note to Physicians:

CONTACT PHYSICIAN IMMEDIATELY

5. Fire Fighting Measures

Flammable Properties:

Flash Point: 63 F

Method:

Hazardous Combustion Products:

NO HAZARDOUS COMBUSTION PRODUCTS ARE KNOWN.

Extinguishing Media:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

Firefighting Procedures:

Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:



2052 FLAT HS CLEAR URETHANE

Page 3 of 5

CONTAIN SPILLAGE, THEN COLLECT WITH NON-COMBUSTIBLE ABSORBENT MATERIAL.

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

NO DANGEROUS REACTION KNOWN UNDER CONDITIONS OF NORMAL USE. STABLE UNDER NORMAL CONDITIONS. VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

Incompatibility:

Alkaline materials, strong acids and oxidizing materials.

Hazardous Decomposition Products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, and possibly acrolein.

Hazardous Polymerization:

WILL OCCUR

11. Toxicological Information

Eye:

SERIOUS EYE DAMAGE/EYE IRRITATION. CATEGORY 2.

Skin:

MAY CAUSE SKIN IRRITATION IN SUSCEPTIBLE PERSONS.

Ingestion:

DO NOT INGEST. CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, AND DIARRHEA.

Inhalation:

INHALATION: DIZZINESS, BREATHING DIFFICULTY, HEADACHES, AND LOSS OF COORDINATION.

Subchronic:

INFORMATION NOT AVAILABLE.

Chronic/Carcinogenicity:

NON CARCINOGENICITY

IARC:

INFORMATION NOT AVAILABLE.

NTP:

INFORMATION NOT AVAILABLE.

OSHA:

INFORMATION NOT AVAILABLE.

12. Ecological Information

Environmental Fate:

INFORMATION NOT AVAILABLE.

Environmental Toxicity:

NO DATA AVAILABLE

Other Adverse Effects:

NO DATA AVAILABLE

13. Disposal Considerations

Waste Disposal Method:

Collect absorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local, state & federal hazardous waste regulations before disposing into approved hazardous waste landfills. Obey relevant laws.

Contaminated Materials:

EMPTY REMAINING CONTENTS. DISPOSE AS UNUSED PRODUCT. DO NOT RE-USE EMPTY CONTAINERS. DO NOT BURN, OR USE A CUTTING TORCH ON, THE EMPTY CONTAINER.

14. Transport Information

DOMESTIC (DOT) SHIPPING DATA:

DOT PROPER SHIPPING NAME.....PAINT, FLAMMABLE LIQUID
DOT HAZARD CLASS.....FLAMMABLE LIQUID
DOT LABELS REQUIRED.....FLAMMABLE LIQUID
DOT PLACARDS REQUIRED.....YES FLAMMABLE
BILL OF LADING DESCRIPTION.....PAINT, FLAMMABLE LIQUID
UN/NA CODE.....UN1263

Environmental Hazards:

CONTAIN ALL SPILLS

Special Precautions for User:

KEEP ALL CONTAINERS CLOSED AND AWAY FROM FLAMES.

15. Regulatory Information

U.S. Federal Regulations:

OSHA:

FLAMMABLE LIQUID, MILD SKIN IRRITANT.

CERCLA: SARA Hazard Category:

FIRE HAZARD AND HEALTH HAZARD

Section 313:

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

N = N.T.P. Carcinogen

I = I.A.R.C. Carcinogen

There are no heavy metals or carcinogen in this coating.

US State Regulations:

NO DATA AVAILABLE

Volatile Organic Compounds:

SEE TECH DATA SHEET.

16. Other Information

Prepared By:

RANDY KONTZ

Information Contact:

RANDY KONTZ

Manufacturer Disclaimer:

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by this company to be accurate.

HEALTH:	2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	B

