



## **V-2062 CLEAR GLOSS WATERBASE SEALER**

## **TECHNICAL DATA SHEET**

**PRODUCT DESCRIPTION:** V-2062 Clear Waterbase Sealer is formulated with special chemicals combined with a special acrylic polymer for use on tiles

**APPLICATION:** Dipping, Conventional, Airless Spray Systems. Reduce with water if necessary.

**SURFACE PREPERATIONS:** For best results it is important that all surface contaminants, such as moisture, oil, dirt, etc. be removed before application

### **PHYSICAL INFORMATION**

**COLOR:** CLEAR & TINTABLE

**GLOSS:** GLOSS

**SOLIDS BY WEIGHT:** 45%

**RECOMMENDED DRY FILM THICKNESS:** 1.5-2.0 mils

**THEORETICAL COVERAGE:** 400 SQ FT PER GALLON

### **DRYING TIME @ 72 F**

**TO TOUCH:** 10 MINUTES

**TO HANDLE:** 30-60 MINUTES

### **REGULATORY DATA**

**FLASHPOINT:** 218 F

**PRODUCT WEIGHT:** 8.84 LBS/GAL

**MATERIAL VOC:** 0.69 POUNDS PER GALLON / 83 GRAMS PER LITER

**COATING VOC:** 1.15 POUNDS PER GALLON / 138 GRAMS PER LITER



## APPLICATION

## TECHNICAL DATA SHEET

**MIXING:** This material is a one-component coating and should always be mixed thoroughly with a power agitator before application.

**MIX RATION:** Not applicable

**WORKING POT LIFE:** Not applicable

**AIRLESS SPRAY:** Suitable

Tip Range 15-17 thou (0.38-0.43mm)  
total output fluid pressure at spray tip not less than 2,500 P.S.I.

**AIR SPRAY:** Suitable  
(Pressure Pot)

Gun	DeVilbiss	MBC or JGA
Air Cap	704	
Tip	E	

**BRUSH:** Suitable

Typically 1.5-2.0 mils can be achieved. Care should be taken to avoid under application.

**ROLLER:** Suitable

Typically 1.5-2.0 mils can be achieved. Care should be taken to avoid under application.

**THINNER:** Water

Do not thin more than allowed by local environmental legislation when applicable.

**CLEANER:** Water

**WORK STOPPAGES:** Thoroughly flush all equipment with water. All unused material should be stored in tightly closed containers. Partially filled containers may show surface skinning and/or viscosity increase of the material after storage. Material should be filtered prior to use.

**CLEAN UP:** Clean all equipment immediately with water. It is good working practice to periodically flush out spray equipment during the course of the working day. Frequency of cleaning will depend upon amount sprayed, temperature and elapsed time, including any delays.

All surplus materials and empty containers should be disposed of in accordance with appropriate regional regulations legislation.

## SYSTEM COMPATIBILITY:

N/A

## SHIPPING & STORAGE

**NUMBER OF COMPONENTS:** 1

**PACKAGED IN:** Totes, 55-Gallon Drums, 5 Gallon Pails, and 1 Gallon Cans.

**STORAGE TEMPERATURE:** Minimum 20 F. Maximum 1