

8 3 6 5 W - 2 6 7

1/2 HP AC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

A complete, reliable solution with powerful performance.



KEY FEATURES

VALUE
Package

CONSISTENT AND DEPENDABLE
Operation

WI-FI
Built In

RELIABLE

1/2 HP AC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

WARRANTY LIFETIME MOTOR, 1-YEAR PARTS.

SECURE

SECURITY+ 2.0® SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ®.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MyQ TECHNOLOGY ALLOWS USERS TO KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

INCLUDED ACCESSORIES:

MULTI-FUNCTION CONTROL PANEL®

Turns on garage door opener lights from inside the garage.



882LMW

(2) 3-BUTTON REMOTE CONTROLS

Operate up to 3 openers or MyQ Light Accessories each.



893LM

WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



877LM

POWERFUL ADD-ONS:

MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



374UT

REMOTE LIGHT CONTROL

Enables home lighting control through a garage remote or a smartphone.



825LM

REMOTE LIGHT SWITCH

Replaces an existing wall switch to enable home lighting control with a garage remote or smartphone.



823LM

DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house.



829LM

PRODUCT GUIDE 8365W-267

1/2 HP AC CHAIN DRIVE WI-FI
GARAGE DOOR OPENER

LiftMaster®

MASTERFUL ENGINEERING.

MOTOR

- 1/2 Horsepower AC
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (16:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **AC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)



DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	10'	10'

Headroom Clearance Required: 2"

7"
Per second for door to move upward

7"
Per second for door to move downward

STANDARD SPECS.

SECURITY

RADIO CONTROLS

Operating Range: **~200'**
Operating Temperature: -35°F to 150°F

- SECURITY+ 2.0®**
(2) 3-Button Remote Controls (893LM) and Wireless Keyless Entry (877LM)
- Remote Controls: 310, 315 and 390 MHz Tri-Band*
 - Keyless Entry: 310, 315 and 390 MHz Tri-Band*
 - Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
 - Anti-Burglary Coding
- *Tri-band on Security+ 2.0 coding only.

- ENCRYPTED CONTROLS**
Multi-Function Control Panel® (882LMW)
- Program Remote Controls
 - Maintenance Alert System
 - Easy Wi-Fi Setup

SMART

MyQ® RADIO

902-928 MHz
50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 2 100-Watt Lightbulbs
- Solid-State Light Delay
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

SHIPPING.

SHIPPING WEIGHT
(in lbs.)



CARTONS (2)

- CARTON 1:** 20" x 12" x 10"
 - Garage Door Opener Head (8365W)
 - Multi-Function Control Panel (882LMW)
 - (2) 3-Button Remote Controls (893LM)
 - Wireless Keyless Entry (877LM)
 - The Protector System® Safety Reversing Sensors
- CARTON 2:** 10'4" x 5" x 5" (for 7' Rail)
 - Assembled Solid-Steel Chain T-Rail

CONVENIENCE AND SAFETY.

- Alert-2-Close/Unattended Close Operation (with Select Accessories)[†]
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices

